

Hi-Stream H.264 IP MEGAPIXEL NETWORK CAMERA

- FEATURES -

1. H.264 Video Compression (**Real-Time**)
2. 1/3 Sony Super HAD CCD Sensor
3. Supports SD Card Backup
4. 2-way Audio
5. D1 High Resolution Recording
6. Simple Installation
7. Supports dual IP streaming
8. 16 Channel NVR Recording Software
9. Lens not included



- SPECIFICATION -

Hi-Stream H.264/AVC IP Solution

MODEL	IPCAM-1-Q
Video Standard	PAL / NTSC
SDRAM	64MB
FLASH	8MB
Image sensor	1/3" Sony Super HAD CCD
Lens Changeable	CS Mount
I/O	2 in/ 2 out
RS-485	Yes
Microphone Plug	Yes
Audio Out	1
Power Consumption	DC 12V, 500 m/A
Dimensions	2.24(W) x 2.09(H) x 4.13(D) Inch
Network	RJ45
Ethernet	10/ 100 Base-T
Network Protocol	HTTP, TCP/ IP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP
System	Embedded Linux OS
Video Resolution	D1: 720x576(PAL) - 720x480(NTSC) 4CIF: 704x576(PAL) - 704x480(NTSC) 2CIF: 704x288(PAL) - 704x240(NTSC) DCIF: 528x384(PAL) - 528x320(NTSC) CIF: 352x288(PAL) - 352x240(NTSC) QCIF: 176x144(PAL) - 176x120(NTSC)
Video adjust	Brightness, Contrast, exposure, sharpness
Image snapshot	Yes
Full screen monitoring	Yes
Compression format	H.264
Video bitrate adjust	CBR, VBR
Motion Detection	Yes all areas
Triggered action	Save to SD card
Pre/ Post alarm	Yes, configurable
Security	Password protection
Firmware upgrade	HTTP mode, can be upgraded remotely
Simultaneous connection	Up to 10
Audio	2-way
SD card management	Yes
Video playback	Yes
Delete files	Yes
Web browsing requirement	Microsoft IE 6.0 or above
OS	Windows 2000, XP, 2003
Hardware	Suggested Intel-C 2.0G, RAM: 512MB, Graphic card: 64MB
	Minimum Intel-C 1.6G, RAM: 256MB, Graphic card: 32MB